



LTC 0485 Series DinionXF Color Cameras



- ▶ 15-bit DSP technology
- ▶ XF-dynamic
- ▶ Bilinx communication
- ▶ NightSense
- ▶ Default shutter
- ▶ Lens wizard
- ▶ Auto black
- ▶ Video motion detection
- ▶ 540 TVL resolution

The LTC 0485 Series of High Performance 1/3-inch Digital CCD Color Cameras create the best possible image, even under the most difficult light and scene conditions. Based on unique 15-bit digital video processing technology and employing XF-Dynamic, these cameras provide excellent sensitivity with extended dynamic range. By employing the best 1/3-inch CCD available, advanced front end processing, combined with the outstanding Dinion DSP, the cameras achieve an astonishing sensitivity, providing better color images in low light situations and sharper daytime images. Intelligent White balance algorithms, supported by a White Balance Hold function and even full manual white balance, ensure the most accurate color reproduction possible. All Dinion cameras are supplied ready to operate. Simply attach and focus the lens, and connect power to provide optimal pictures under virtually all scene conditions. No tools are required for back focus and power connection. For extra challenging situations where fine tuning or special settings are required, the camera parameters can be individually set using the control buttons on the side of the camera and On-screen Display (OSD). Also, to aid installation, the camera automatically detects the lens type, and using the Lens Wizard ensures accurate (back) focusing for perfectly sharp pictures at all times

Functions

XF-Dynamic

Extended dynamic range is brought to a new level on the LTC 0485 Series Camera by XF-Dynamic technology. XF-Dynamic automatically processes the highly accurate 15-bit digital signal to optimally capture the detail in both the highlight and lowlight areas of the scene simultaneously, to maximize the information visible in the picture.

Bilinx Technology

The LTC 0485 series cameras incorporate Bilinx. Bilinx is a bidirectional communication capability embedded in the video signal of all Bosch Dinion cameras. With Bilinx technicians can check status, change camera settings and even update firmware from virtually anywhere along the video cable. Bilinx reduces service and installation time, provides for more accurate set-up and adjustment, and improves overall performance. In addition, Bilinx uses the standard video cable to transmit alarm and status messages, providing superior performance without additional installation steps.

Video Motion Detection

The built-in video motion detector allows you to select up to four fully programmable areas with individual

thresholds. The global scene change detector minimizes false alarms caused by sudden lighting condition changes, such as switching on or off the indoor or security lighting. When motion is detected alarms may be displayed in the video signal, the output relay can be closed in addition to alarm message transmission on Bilinx.

Auto Black

The automatic black level feature, enhances contrast by removing veiling glare from the picture or when contrast is reduced by fog or mist.

Default Shutter

When viewing moving objects a fast shutter speed is required. When using a fast shutter speed the lens opening or gain control needs to be increased to maintain the video signal. The camera sensitivity is limited by the fast shutter speed. The default shutter setting of the LTC 0485 offers the best of all worlds, fast shutter speed as long as there is sufficient light, however as the light level falls, when other adjustments have been exhausted, the shutter reverts to the standard setting maintaining the cameras excellent sensitivity.

Back Light Compensation (BLC)

Offering a fully programmable BLC area of interest, and a variable BLC level, the camera can be easily set up for even the most challenging entrance applications.

Lens Wizard

The LTC 0485 series automatically detects the type of lens installed. The Lens Wizard will focus the lens at the maximum lens opening, to ensure that focus is maintained throughout the entire 24-hour day/night cycle. No special tools or filters are required.

Programmable Modes

The camera supports three independent operating modes. The 3 modes are preprogrammed for typical applications, but are fully programmable for individual situations. Switching between modes is easy via Bilinx or the external alarm input.

NightSense

The LTC 0485 cameras feature NightSense. With NightSense the sensitivity is increased by 9 dB in monochrome mode. NighSense can be automatically activated in low light situations, or remotely using Bilinx.


SensUp

By increasing the integration time on the CCD up to 10 times, the effective sensitivity is dramatically enhanced, especially useful where there is no artificial lighting and you rely on the moon, stars and scattered radiation.

Certifications and Approvals

Electro Magnetic Compatibility	
Emission	EN55022 class B, FCC class B part 15
Immunity	EN50130-4 Alarm Systems, Part 4
Vibration	Camera with 500 gr (1.1 lbs) lens according to IEC60068-2-27
Safety	
LTC 0485/11 and LTC 0485/51: EN60065	
LTC 0485/21 and LTC 0485/61: UL6500, cUL CAN/CSA E60065-00	

Installation/Configuration Notes



Dimensions in mm (inches)

Parts Included

Quantity	Components
1	LTC 0485 Series Dinion ^{XF} Color Camera
1	Spare male 4 – pin lens connector
	Lens not included

Technical Specifications

Electrical

Model No.	Voltage Range	
LTC 0485/11	12 - 28 VAC 11 - 39 VDC	45 - 65 Hz
LTC 0485/21	12 - 28 VAC 11 - 39 VDC	45 - 65 Hz
LTC 0485/51	85 - 265 VAC	45 - 65 Hz
LTC 0485/61	85 - 265 VAC	45 - 65 Hz
Power Consumption	4 W	
Imager	Interline transfer CCD 1/3-inch format	
Active Pixels		
PAL	752 H x 582 V	
NTSC	768 H x 492 V	
Sensitivity (3200 k)		
Sensitivity (Full Video) ¹⁾	2.4 lux (0.24 fc)	
Sensitivity 50 IRE ¹⁾	0.59 lux / 0.24 lux (NightSense) (0.059 fc / 0.024 fc (NightSense))	
Minimum Illumination ¹⁾	0.24 lux / 0.10 lux (NightSense) (0.024 fc / 0.01 fc (NightSense))	
Minimum Illumination with SensUp	0.024 lux / 0.010 lux (NightSense) (0.0024 fc / 0.0010 fc (NightSense))	
Horizontal Resolution	540 TVL	
Signal-to-Noise-Ratio	> 50 dB	
Video Output	1 Vpp, 75 ohm	
Y/C Output	Y: 1 Vpp / C: 0.3 Vpp	
Synchronization	Internal, line lock, HV-lock and genlock (Burst lock) selectable	
Electronic Shutter	Auto (1/60 (1/50) to 1/500000), fixed, flickerless, default	
Sensitivity up	Off, automatic continuous up to 10x	
Auto Black	On, off selectable	
Range	32x dynamic range enhancement	
Dynamic Noise Reduction	Auto, off selectable	
Contour	Sharpness enhancement level selectable	
BLC	Off, area and level selectable	
Gain	Auto (maximum level selectable to 28 dB) or fixed level selectable	
White Balance	ATW (2500 - 10000 K), AWB hold, Manual WB se- lectable	
VMD	4 area, sensitivity selectable	
Alarm Output	VMD or Bilinx	
Alarm Input (TTL)	Profile switching, +5 V nominal, +40 VDC max.	
Alarm Output Relay	max. 30 VAC or +40 VDC, max. 0.5 A continuous, 10 VA	
External Synchronal-Input	75 ohm or High Impedance selectable	

Cable Compensation Up to 1000 m (3000 ft) coax without external amplifiers
(automatic set-up in combination with coaxial communi-
cation)

Camera ID 16 character editable string, position selectable

Lens Types Manual, DC- and Video-iris auto-detect with override DC-
iris drive: max. 50 mA continuous Video-iris: 1.1.5 ± 0.5
VDC, max. 50 mA continuous

Remote Control Bi-directional coaxial communication

1) F1.2, 89% reflection, SensUp Off

Mechanical

Dimensions 59 x 67 x 122 mm (2.28 x 2.6 x 4.8 inch)
(H x W x L) without lens

Weight 450 g (0.99 lbs) without lens

Tripod Mount Bottom (isolated) and top 1/4-inch 20 UNC

Lens Mount C and CS

Controls OSD with softkey operation

Environmental

Operating Tempera- -20 °C to +50 °C (-4 °F to +122 °F)
ture

Storage Temperature -25 °C to +70 °C (-13 °F to +158 °F)

Operating Humidity 20% to 93% RH

Storage Humidity up to 98% RH

Ordering Information

Model | Description

LTC 0485/11 DinionXF Color Camera
1/3-inch, high performance, 540 TVL, PAL, DSP, 12 – 28 VAC/11 – 39 VDC,
50 Hz

LTC 0485/21 DinionXF Color Camera
1/3-inch, high performance, 540 TVL, NTSC, DSP, 12 – 28 VAC/
11 – 39 VDC, 60 Hz

LTC 0485/51 DinionXF Color Camera
1/3-inch, high performance, 540 TVL, PAL, DSP, 85 – 268 VAC, 50 Hz

LTC 0485/61 DinionXF Color Camera
1/3-inch, high performance, 540 TVL, NTSC, DSP, 85 – 265 VAC, 60 Hz

Hardware Accessories

LTC 3364/21 Varifocal Lens IR corrected
1/3-inch, 2.8 – 6 mm, DC-iris, CS-mount F1.4-200, 4-pin

LTC 3364/31 Varifocal Lens
1/3-inch, 3.5 – 8 mm, DC-iris, CS-mount F/1.4-200, 4-pin

LTC 3364/40 Varifocal Lens
1/3-inch, 2.8 – 12 mm, DC-iris, CS-mount F1.4-360, 4-pin

LTC 3374/20 Varifocal Lens
1/3-inch, 5 – 50 mm, DC-iris, CS-mount F1.4-185, 4-pin

LTC 3384/21 Zoom Lens
1/3-inch, 6 – 60 mm, DC-iris, CS-mount F1.4-360, 4-pin

TC 120PS Power Supply Unit
110-120 VAC/15 VDC, 50/60 Hz, 300mA

TC 220PS Power Supply Unit
230 VAC/15 VDC, 50 Hz, 10 VA

Ordering Information

Model | Description

TC 220PSX-24 Power Supply Unit
230 VAC/20 VAC, 50 Hz, 20 VA

TC 1334 Power Supply Unit
120 VAC/24 VAC, 60 Hz, 30 VA

Software Options

VP-CFGSFT Configuration Software
for cameras using Bilinx, includes VP-USB Adaptor

Americas:
Bosch Security Systems
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 585 223 4060
Fax: +1 800 289 0096
security.sales@us.bosch.com
www.boschsecurity.us

Europe, Middle East, Africa:
Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 (0) 40 27 83955
Fax: +31 (0) 40 27 86668
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:
Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by